



 **actiLib**

actiLib AutoLoader 1U:

The actiLib AutoLoader is ideal as an entry-level automated backup solution for small to medium sized businesses. It combines storage density and tape library features in a compact 1U form factor. Providing high capacity data storage in a compact 1U form factor, with advanced features as a bar code reader and web based remote management, all included in an entry-level automated backup solution.

Product Highlights:

- **Exceptional storage density value**

actiLib AutoLoader packs the maximum amount of storage into the minimum amount of space. LTO-4 tape technology delivers 12.8 TB of compressed capacity (2:1) in a 1U form factor.

- **Easy to install, manage and use integrated solutions**

Standard barcode reader provides faster inventory times and facilitates tracking of media

- **Alternatives in movement and storage of data**

For dedicated import/export of media cartridges, each AutoLoader includes one mail slot. The AutoLoader also includes 2 removable 4-slot magazines for bulk loading of media, and provides a convenient bulk storage unit for moving media offsite.

- **Agility - Easy to manage**

Integrated web-based remote management capability allows a remote administrator to control, configure, monitor and troubleshoot the device, thus relieving the customer of costly onsite IT resources

- **Flexible and compliant with future tape technology**

actiLib AutoLoader supports both LTO-3 HH (SCSI) and LTO-4 HH with SCSI, SAS and Fibre channel interface and is prepared for LTO-5

- **Customer serviceable and replaceable components**

Easy to manage modular design of tape AutoLoader allows for quick service or repair of unit to reduce downtime and maximize efficiency.

actiLib AutoLoader 1U

Manage your media easily with the standard features include a bar code reader and two removable 4-slot magazines. Perfect for replicated systems, the web-based remote management interface reduces dependencies on local IT staff, allowing multiple sites to be supported centrally.



	LTO-3 Half Height	LTO-4 Half Height
General		
Capacity (native/compressed)	3.2TB / 6.4TB	6.4TB / 12.8TB
Max Performance	432 GB/hr	576 GB/hr
Interface	SCSI	SCSI, Fibre Channel, SAS
No. of Drives	1	
No. of Slots Available	8	
Form Factor	1U (19" Rackmount)	
Reliability		
Robotics MTBF	500,000 swaps	
Access and Operation		
Remote Management (Web)	Yes	
WORM (Write Once Read Many)	Yes	
Hardware Encryption	No	Yes
Environments		
Temperature (Operating)	10°C - 35°C (50F - 95F)	
Temperature (Non-operating)	-30°C - 60°C (-40F - 140F)	
Relative Humidity (Operating)	20 - 80% (non-condensing)	
Relative Humidity (Non-operating)	20 - 80% (non-condensing)	
Accessories		
Included	Rackmount Kit	
Dimensions		
Width	48.2cm	
Depth	80.9cm	
Height	4.4cm	
Weight (no tapes)	11.5kg (base)	

For more information, please contact your Authorized Distributor or Reseller.