



 **actiLib**

actiLib Library 2U LTO:

The actiLib Library 2U is ideal as an entry-level solution for those application environments that demand automated storage while at the same time being kind to your budget. It is easy to install, user friendly and enables unattended backup to be configured. Its sleek 2U design not only fits 19 inch rack systems but also lends itself to table top use. Leading backup applications support the actiLib Library 2U that accepts its commands via the intelligent Drive SCSI interface using LUN masking thus saving valuable connections.

Product Highlights:

- **High Data Density in a small foot print**

The highly efficient cartridge layout allows for a 2U design and so minimises 19 inch Rack space consumption. Maximum capacity assuming a 2:1 compression ratio is 16,8 TBytes of data.

- **Easy to install into existing IT Infrastructures**

Integrated Web-Based Remote Management enables the administrator to configure and maintain the library from the workplace and does away with the need for hands-on setup.

- **Standard Bar Code Reader**

The time to initialise the machine is greatly reduced through the use of the standard Bar Code Reader. It simplifies the addition of cartridges into the backup scheme and facilitates keeping track of data

- **Magazines and Mailslot**

All tapes are kept inside of two Magazines that are easily injected and ejected and allow for bulk loading. In addition, a Mail Slot safeguards non-disruptive operation of and positively affects the completion time of backup jobs.

- **Flexible and compliant with future tape technology**

actiLib AutoLoader supports both LTO-3 HH (SCSI) and LTO- 4 HH with SCSI, SAS and Fibre channel interface and is prepared for LTO-5

- **Easy to maintain and service**

The Power Supply, Controller Unit, Tape Drive and Robot can all be exchanged on-site offering decisive advantages in resuming the backup.

actiLib Library 2U LTO

In areas that previously dictated the use of mid-range libraries, the actiLib Library low profile, high cartridge count and flexibility of use make it ideal for those environments. Its commanding design, small footprint, flexibility and service-friendliness make it the logical choice for continued data protection and enhances the network's overall reliability.



	LTO-4 Half Height	LTO-4 Full Height
General		
Capacity (native/compressed)	19.2 TB / 38.4 TB	19.2 TB / 38.4 TB
Max Performance	1728 GB/hr	864 GB/hr
Interface	SAS, SCSI, Fibre Channel (FC)	SCSI, Fibre Channel
No. of Drives	2	1
No. of Slots Available	24	
Form Factor	2U (19" Rackmount)	
Reliability		
Robotics MTBF	500,000 swaps	
Access and Operation		
Remote Management (Web)	Yes	
WORM (Write Once Read Many)	Yes	
Hardware Encryption	Yes	
Environments		
Temperature (Operating)	10°C - 35°C (50F - 95F)	
Temperature (Non-operating)	-30°C - 60°C (-40F - 140F)	
Relative Humidity (Operating)	20 - 80% (non-condensing)	
Relative Humidity (Non-operating)	20 - 80% (non-condensing)	
Accessories		
Included	Rack mount Kit	
Dimensions		
Width	48.2 cm	
Depth	74 cm	
Height	8.76 cm	
Weight (no tapes)	12 kg	

For more information, please contact your Authorized Distributor or Reseller.